

GS-7260

5-PORT IGMP | GIGABIT SWITCH



PRODUCT OVERVIEW

Comtrend's GS-7260 5-Port IGMP Switch offers IGMP snooping and 5 Gigabit Ethernet ports for the most bandwidth-intensive applications. The GS-7260 is ideal for video streaming because it reduces the Multicast traffic passing through your switch, enhancing your streaming video experience.

Note: This switch supports IGMP v1 & v2

KEY BENEFITS

Optimized Video Streaming

IGMP snooping is designed to improve video quality and minimize video lag

Super-Fast Wired Connectivity

Gigabit ports-10x faster than standard ports

Maximize your Internet Experience

Superior performance through a direct wired connection

Eco-Friendly Solution

Supports IEEE802.3az to effectively reduce power consumption

DS_GS-7260_V2016.4

GS-7260



5 Gigabit Ethernet Ports

Power Plug

FEATURES

- Supports auto MDI/MDI-X crossover detection and auto correction.
- Supports full and half duplex for 10/100Mbps, and full duplex for 1000Mbps
- Store-and-forward architecture filters fragment & CRC error packets
- Wire-speed packet filtering and forwarding rate

SPECIFICATIONS

Interface

- 5 RJ-45 Gigabit Ethernet Ports

MAC Address Table

- 2K

Buffer Memory

- 128K Bytes

LED Indications

- 1 Power LED (Power: Green)
- 5 Port LEDs (Link/Activity)
 - Amber: 10/100Mbps
 - Green: 1000Mbps

Power

- External Power Supply 5V/1A

Power Consumption

- MAX DC Input 2.129W

Safety

- CE, LVD

Dimensions

- 3.90 x 2.67 x 0.96in; 99 x 67.7 x 24.5mm

Weight

- 110g; 3.88oz

Case

- Plastic

Temperature

- Operating: 32~104°F (0~40°C)
- Storage: -4~158°F (-20~70°C)

Humidity

- Operating: 10~90% RH (Non-Condensing)
- Storage: 5%~90% (Non-Condensing)

EMC

- FCC, CE Class B

Note: Specifications subject to change without notice.

DS_GS-7260_V2016.4