



**SOFTWARE  
RELEASE NOTES**

Version  
**1.3.0.11**

**For Model WAP-EN1750R**

Release Date: June 2018

## Revision Summary

Software Version	Description	Release Date
1.3.0.11	Release# 20180228	June 2018
1.2.0.3	Release# 20170412	June 2017

## Changes and Fixes

- New version of NMS feature (version: 1.3.3.0)
- Added support for multiple web login.
- Added support for client signal to shows in dB and % at the web page dashboard.
- Added Repeater mode and Client Bridge mode in the operation feature.
- Added band steering feature in AP mode.
- Support 802.11r standard in AP mode.
- Added network filter for Guest SSID network.
- Added support for external captive portal (WTP only).
- Added support for HTTP/HTTPS port configuration via web GUI.
- Added a patch for KRACK vulnerability.
- Fixed an issue where TR-111 unable to be configure manually.
- Change the encryption mode to set at WAP2-AES for the WifiXtend feature.
- Added support for DFS channel.
- Fixed an issue where the client device gets wrong DNS IP address if the AP is in repeater mode with static IP address.
- Fixed an issue to where a controller cannot push traffic shaping configuration to the managed AP.
- Fixed an issue to where a controller cannot push bandsteering configuration to the managed AP.
- Fixed an issue to where a controller cannot push layer2 filter configuration to the managed AP.
- Fixed an issue where external captive portal doesn't worked properly on a managed AP mode.

## Known Issues

- None

## Access Default Settings

AP LAN IP Address: 192.168.2.2

Username/Password: admin/1234

## Prior Releases

**1.2.0.3**

- Fixed the Guest Network / Traffic Shaping setting doesn't work properly.
- Fixed the outdoor monitor feature.
- Support TR-069 feature.
- Removed the NMS feature mode.
- Support Captive Portal feature.
- Support SNMP write feature.
- Support Fast Roaming feature (802.11r/k).
- Support Captive Portal guest data limitation.
- Support Comtrend WifiXtend feature
- Support TR-111 (STUN client)
- Compatible with NMS controller version: 1.3.1.0

**1.0.0.0**

- First version

## Upgrade Procedure

1. Upgrade Software
  - a. Assign a 192.168.2.x/24 static IP address on your computer. Where x is a number in the range of 3-100.
  - b. Open a web browser, connect to 192.168.2.1, and login with username **admin** and password **1234**.
  - c. Click on **Advanced** → **Update Firmware**: Software Upgrade. Click on “Browse” button
  - d. Locate and double click on the appropriate Comtrend software image
  - e. Click on “Update” button. You will be informed that the product will become unresponsive and to not turn off or unplug the product, click “OK”. New window will pop-up showing the progress of uploading the software. Upon completion, the GUI page will be redirected to the log-in page.
2. Verify
  - a. Log-in to the GUI.
  - b. Information section of the GUI shows the “Image version”. Verify that the latest code reflects: 1.2.0

## Technical Support

For technical support contact your Sales Engineer or Comtrend Technical Support at 949-753-9640, Option 3. You can also submit questions and comments at <http://us.comtrend.com/contact-us/>

## RMA Request

An RMA can be initiated at <http://customersupport.comtrend.com/>

The contents of this document are current as of the date of publication. Comtrend Corporation reserves the right to change the contents without prior notice. In no event will Comtrend Corporation be liable for any damages or for commercial losses resulting from information contained in this document.

### Comtrend Corporation

14 Chrysler  
Irvine, CA 92618  
(949) 753-9640