



Quick Guide

G.hn Powerline:

PG-9172, PG-9172PT, PG-9171n, PG-9172AC, PG-9172PoE, PG-9182PT

Firmware Upgrades Via GUI

Version 1.0, July 13, 2018



Upgrade Firmware

Visit the User Interface. Then navigate to the “Device” page which allows you to update the system firmware to a more recent version. Updated firmware versions often offer increased performance and security, as well as bug fixes. You can download the latest firmware from the Comtrend website.

Hardware information	
•Device name	PG-9172PoEv2
•Device description	Ghn Ethernet and PoE to Powerline Adapter
•Device manufacturer	Comtrend
•Serial number	1819173POEF-A9000007
•MAC address	64:68:0c:ff:ae:d0
•HW version	1_0
Software information	
•FW version	PG-9172PoEv2-66R49733CTU-C01_R01
•System uptime	1 days, 21h 18m 40s
Security	
•New Configuration password	<input type="text"/>
	<input type="button" value="Ok"/> <input type="button" value="Cancel"/>
SW update	
•Status	Ready: initial status
•Protocol	<input type="button" value="FTP"/> ▾
•Server IPv4/v6	<input type="text"/>
•FTP User	<input type="text"/>
•FTP Password	<input type="text"/>
•OSUP Filename	<input type="text"/>
	<input type="button" value="Ok"/> <input type="button" value="Cancel"/>
HTTP SW update	
•Upgrade file:	<input type="button" value="Choose File"/> No file chosen
	<input type="button" value="Ok"/> <input type="button" value="Cancel"/>



Do not switch off or disconnect the device during a firmware upgrade, as this could damage the device.

HTTP SW Update	Software update section that will allow a consumer to update the PLC to a newer firmware from the device User Interface.
Upgrade file:	Click “Choose File” to select the firmware file located on your computer.
Click “OK” to begin the upgrade process.	